

/ Descriptions

TO-252



Ultrafast Recovery Diode in a TO-252 Plastic Package.

/ Features

Silicon epitaxial process to produce ultrafast recovery diode with low reverse leakage current and high reliability.

/ Applications

For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit**/ Pinning**

PIN1 NC

PIN 2 Cathode

PIN 3 Anode

PIN 4:Case

/ h_{FE} Classifications & Marking






See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	600	V
Working Peak Reverse Voltage	V_{RMS}	420	V
Average Rectified Forward Current	I_F	8	A
Non Repetitive Peak Surge Current	I_{FSM}	125	A
Thermal resistance, junction to case	$R_{\theta Jc}$	3.5	°C/W
Junction and Storage Temperature Range	T_j T_{stg}	-55 150	°C


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V_{BR}	$I_R=100\mu A$	600			V
Forward Voltage	V_F	$I_F=8A$ $T_c=25$		1.4	1.7	V
		$I_F=16A$ $T_c=25$		1.7	2.1	V

$-I_F$


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

MUR860

Note:

BR:

Company Code


MUR860

Product Type.

****:

Lot No. Code, code change with Lot No.

() /



Note:

- 1

25 150

60 90sec;
- 2

245±5

5±0.5sec;
- 3

2 10 /sec.
- 1.Preheating:25~150 °C, Time:60~90sec.

2.Peak Temp.:245±5 °C, Duration:5±0.5sec.

3. Cooling Speed: 2~10 °C/sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5℃ Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-252	2,500	2	5,000	5	25,000	13 ×16	360×360×50	385×257×392

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

/ Notices